

Submersible Flat Cables

Features

- › 1100V Grade cable with 99.97% pure ETP grade copper
- › With uniform double insulation, no shock hazards, hence safe to use
- › Lesser cable resistance, hence negligible voltage drop in cable ensures appropriate voltage at motor terminals.



Submersible Cables (Flat Cables) as per IS694 [HSN Code 8544]

Nominal Cross Section Area of Conductor (Sq. mm)	Construction Details / Max Dia (mm)	Current Carrying Capacity at 40°C (A)	Cat. No.	M.R.P. (₹) per Meter
1	14 / 0.3	11	WS00010PECM*.	128
1.5	22 / 0.3	14	WS00015PECM*.	158
2.5	36 / 0.3	18	WS00025PECM*.	253
4	56 / 0.3	26	WS00040PECM*.	365
6	84 / 0.3	31	WS00060PECM*.	545
10	80 / 0.4	42	WS00100PECM*.	950
16	126 / 0.4	57	WS00160PECM*	1450

Note: *5 for 500 mts & 1 for 1000 mts

Note:

- › For all Flat Cables mentioned in this Price List, **HSN code: 8544**, (GST is subject to changes as per Govt. notification)
- › For warranty policy, please refer Agricultural Electrical Products Price List